

Farenhyt



SILENT
KNIGHT

by Honeywell

Fire Alarm Aspiration Sensing Technology®

FAAST XT

General

FAAST XT aspirating smoke detectors deliver highly accurate Very Early Warning Fire Detection over a wide coverage area and offer extensive communication capabilities.

The FAAST XT aspirating smoke detector combines advanced particle separation with unique dual source optical smoke detection technology to provide highly sensitive Very Early Warning Fire Detection while providing enhanced immunity to false alarms. This technology enables FAAST XT to accurately detect incipient fire conditions as early as 60 minutes before a fire actually starts when set for Early Warning and Very Early Warning Fire Detection in applications ranging from mission critical to harsh and extreme environments.

An installed FAAST XT device can protect up to 28,800 sq. ft. (2,676 sq. m) in standard coverage type applications and can be monitored in several different ways, including: Serial or TCP Modbus, Ethernet over a LAN or a direct connection, or via FAAST XT's onboard USB. When connected to a LAN, FAAST XT's email server can provide email event notification to appropriate personnel. FAAST XT also communicates alarm and notifications via form C relays.

PipelQ® is FAAST XT's intuitive design, configuration, and monitoring software. The all-in-one program can be used to create a pipe network tailored to meet site specific requirements, configure a FAAST XT device, and monitor an installed device -- including live trending and reading of historic reports.

* A complimentary download of PipelQ is available at systemsensor.com/faast.

Features

- Provides Very Early Warning Fire Detection, as precise as 0.00046%/ft obscuration
- Five alarm levels and three sensitivity modes provide application flexibility
- User configurable 3-speed fan, allowing for maximum coverage area or minimizing on current consumption
- Ultrasonic flow sensing for each pipe inlet and chamber airflow monitoring for precise system health information
- A single device covers up to 28,800 square feet

Agency Listings



FAAST XT

- Dual source optical detection chamber with enhanced algorithms provide high sensitivity with greater immunity to nuisance conditions
- Patented particle separator removes large, non-fire particulate, ensuring chamber health and extending the life of the field-replaceable filter
- TCP and Serial modbus for easy integration with building management systems
- Easy configuration via USB interface, no external power needed
- Onboard Ethernet interface enables remote monitoring, configuration, web server and e-mail notifications
- Multilingual LCD user interface allows for detailed device information and interaction such as: Active faults, precise airflow monitoring, reset of airflow baseline, test/reset/isolate, and more
- Configurable air flow fault thresholds and verification period
- Convenient wiring compartment
- Status-at-a-glance provides immediate alarm, fault and airflow status

P/N 351566 Rev B

Copyright © 2015 Honeywell International Inc.



FAAST XT User Interface Display

The User Interface consists of 5 Alarm levels – Alert, Action 1, Action 2, Fire 1, and Fire 2, 10 Particulate levels, 10 Bi-color Flow and Fault graph.

Specifications

Electrical

External Supply Voltage	18-30 VDC
Remote Reset Time	External monitor must be pulled low for a minimum of 100 ms
Power Reset	1 sec.
Operating Current	Fan High - 465mA, 11.2W; Fan Med - 340mA, 8.2W; Fan Low - 220mA, 5.3W
Alarm Current	Fan High - 493mA, 11.85W; Fan Med - 368mA, 8.85W; Fan Low - 248mA, 6W
Relay Contact Ratings	3.0 A @ 30 VDC, 0.5 A @ 125 VAC 8 form C, 3 AMP, programmable latching or non-latching

Environmental

Operating Temperature	32°F (0°C) to 100°F (38°C)
Sampled Air Temperature	-4°F (-20°C) to 140°F (60°C)
Humidity Range	10 to 95% (non-condensing)
Sensitivity Range	0.00046% Obs/ft to 6.25% Obs/ft
IP Rating	IP30
Coverage Area	28,800 sq.ft. (2,676 sq.m)
Air Movement	0-4,000 ft./min. (0-1,219 m/min.)

Physical

Dimensions	13.1" W x 13.3" H x 7.5" D (33.274 x 33.783 x 19.050 cm)
Cable Access	4 1-inch (2.54 cm) cable entry holes on top and bottom of unit
Wire Gauge	12 AWG (2.05 mm) max. to 24AWG (0.5 mm) min.
Max Single Pipe Length	400 ft. (123 m) *other three pipes disabled
Total Pipe Length	1050 ft. (320 m) *all designs must be verified within PipeIQ software

Outside Pipe Dim	1.050 inches, IPS (25 mm)
Internal Pipe Dim	0.591 to 0.827 inches (15-21 mm)
Relays	8 form C, 3 AMP, programmable latching or non-latching

Diagnostic Specifications

Event Log	18,000 events stored
Trend Data Log	Configurable sampling period 1 minute to 1 day
Service Log	300 custom user entries

Networking Specifications

Communication Network	Ethernet monitoring, 6 email address alerts, TCP and Serial Modbus
Network Services	DHCP, SMTP, HTTP, MODBUS/TCP, AutoIP, NetBIOS-NS, Serial MODBUS
Ethernet	10/100Mbps, MDI-X
Modbus	TCP or Serial RS-485
Email	6 recipients, selectable notifications
Webserver	Read Configuration, Live View, Logs

Configuration Specifications

PipeIQ	USB or Ethernet
Modbus	Ethernet or RS-485

Ordering Information

9400X	System Sensor Conventional FAAST Fire Alarm Aspiration Sensing Technology
-------	---

Accessories

Various†	UL - Approved Pipe and Fittings
----------	---------------------------------

† Additional accessory information, including part numbers, can be accessed at systemsensor.com/faast.

System Sensor® is a registered trademarks of Honeywell International Inc



This document is not intended to be used for installation purposes. We try to keep our product information up-to-date and accurate. We cannot cover all specific applications or anticipate all requirements. All specifications are subject to change without notice. For more information, contact Silent Knight 12 Clintonville Road, Northford, CT 06472-1610
Phone: (800) 328-0103, Fax: (203) 484-7118. www.farenhyt.com